



FRAME 447TP24
* CLEARANCE TO HOLD
** CONDUIT BOX CAN BE ROTATED IN STEP OF 90°
***MAX. DOWN THRUST : 4P = 11500 lbs
6P = 14500 lbs

Coupling kits no.	BX	BY	BZ	XM	XR	KEYWAY	
						WIDTH	DEPTH
D34-02072-92	1.501	1/4-20UNC	2.125	0.63	2.20	0.375	0.140
D34-02072-93	1.688		2.500				0.203
D34-02072-94	1.938		3/8-16UNC			3.250	0.500
D34-02072-95	2.001	0.226					
D34-02072-96	2.188	N/A				N/A	N/A
D34-02072-97	2.251						
D34-02072-91	1.501						

OUTPUT HP	POLE	VOLT	FREQ.	SYN. R.P.M.	BEARING LOWER SIDE 6218ZZ UPPER SIDE 7230DT	APPROX WEIGHT 2880lb	FILE NO. : CUSTOMER : PO. NO. : ORDER NO. :
TYPE TEFC	FORM VHS	INS. CLASS F	RATING	FRAME 447TP	PROTECTION IP 56		
	REV MARK	APPROVED BY C.P.SYU		CHECKED BY C.P.SU		TITLE OUTLINE FOR THREE PHASE INDUCTION MOTOR	
	DATE	SCALE	DESIGNED BY J.J.SYU		DRAWING BY J.J.SYU		
	APPROVED BY	UNIT inch					
	REVISED BY						
	CONTENT						
						DRAWING NO. AS-071387	
						REV.MARK 00	